

## TECHNICAL SPECIFICATIONS

- Model:** Signature 8080 Mini Advanced
- Size:** Main unit: 11.75" H\* x 21.5" W x 15.5" D (30cm H\* x 55cm W x 39cm D)  
Footprint: 21.5" W x 15.5" D (55cm W x 39cm D)  
\*Overall height including Spindle Control Wire: 30" (76cm)
- Weight:** 69 lbs. (31 kg.)
- Power:** 110/120V, 60Hz or 230/240V, 50Hz
- Max. Operating Current:**  
3A
- X-Y Travel:** 6" x 8" (15.24cm x 20.32cm)
- Spindle Traversing Speed:**  
1.5"/sec (38mm/sec) max. engraving speed  
2.6"/sec (66mm/sec) max. positioning speed
- Z-axis Travel:** 1" (25.4mm)
- Spindle Force:** Surface Sensing, Adjustable, ~1-10 lb. ±1 lb. (~0.5-4.5 kg ±0.5 kg.)
- Cylindrical Capacity:**  
5" (127mm) diameter
- Spindle Type:** Top loading, 11/64" (4.36mm) diameter
- Rotary Cutter (Spindle) Motor:**  
Power: 0-90VDC  
Speed: Adjustable, ~0-10000 RPM  
Horsepower: 1/12 HP
- Illumination:** One 40W appliance bulb (120V or 240V)
- Current Overload Protection:**  
110/120V – One 3A, 250V Slow Blow Fuse (1/4" x 1-1/4")  
230/240V – Two 2A, 250V Slow Blow Fuses (5mm x 20mm)
- Residual Current Protection:**  
Equipment Leakage Current Interrupter (ELCI) Module  
Protects against residual current greater than 10mA
- Data Transmission:**  
RS232 Serial Cable